



PORTABLE GAS ANALYSER | LANDFILL & CONTAMINATED LAND

The Geotech GA5000 is a landfill and contaminated land portable gas analyser, with available gas measurements of CH₄, CO₂, O₂, H₂S and CO. It is easy to use and calibrate, benefiting from our market leading reliability and helping you to standardise monitoring routines, whilst supporting environmental legislation compliance.



SECTOR

- Landfill
- Land remediation

APPLICATIONS

- Landfill gas monitoring
- Waste to energy
- Site investigation
- Contaminated land

FEATURES

- Certified: ATEX, IECEx, CSA, MCERTS and UKAS calibration (ISO17025)
- Measures % CH₄, CO₂, and O₂
- Measures barometric pressure and relative pressure
- Peak and previous readings shown
- Choice of user settings and simple gas reading function
- Simultaneous display of all gases
- 3 year warranty
- CH₄ and CO₂ accuracy ± 0.5% after calibration
- Modular and upgradeable
- Memory: 2,000 IDs* and 4,000 readings (* with GAM software)
- Data logging and profiling function
- Up to 6 gases monitored

BENEFITS

- Easy to use and calibrate
- Supports environmental legislation compliance
- Market leading reliability
- Standardises monitoring routines
- Easy transfer of data

OPTIONS (AVAILABLE AT PURCHASE OR LATER)

- Choice of additional gases including:
 - H₂S to 10,000ppm
 - H₂ compensated CO - up to 10,000ppm (1%)
- Borehole gas flow (l/h)
- Flow logging for improved borehole analysis
- GPS / field navigator
- Gas Analyser Manager software for data download
- ATEX certified anemometer 0-40 m/s

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

TECHNICAL SPECIFICATIONS

| POWER SUPPLY | | | | |
|---|--|---|--|--|
| Battery type | Rechargeable nickel metal hydride battery pack (not user replaceable) | | | |
| Battery life | Typical use 8 hours from fully charged | | | |
| Battery charger | Separate intelligent battery charger powered from mains supply (100-240V) | | | |
| Charge time | Approximately 4 hours from complete discharge | | | |
| GAS RANGES | | | | |
| Gases measured | CO ₂ and CH ₄ | By dual wavelength infrared sensor with reference channel | | |
| | O ₂ | By internal electrochemical sensor | | |
| | CO (H ₂ compensated), H ₂ S, NH ₃ and H ₂ (optional) | By internal electrochemical sensor | | |
| | A full range of internal gas cells can be specified at the time of manufacture | | | |
| Standard gas cells | Cell | Range | Typical accuracy (range : accuracy) | Typical accuracy (range : accuracy) |
| | CH ₄ | 0-100% | 0-70% : ±0.5% (vol) | 70-100% : ±1.5% (vol) |
| | CO ₂ | 0-100% | 0-60% : ±0.5% (vol) | 60-100% : ±1.5% (vol) |
| | O ₂ | 0-25% | 0-25% : ±1.0% (vol) | |
| Optional gas cells | Cell | Range | Typical accuracy | |
| | CO | 0-500ppm | ±2.0% FS | |
| | CO | 0-1,000ppm | ±2.0% FS | |
| | CO | 0-2,000ppm | ±2.0% FS | |
| | CO (H ₂) * | 0-2,000ppm | ±1.0% FS | |
| | H ₂ S | 0-50ppm | ±1.5% FS | |
| | H ₂ S | 0-200ppm | ±2.0% FS | |
| | H ₂ S | 0-500ppm | ±2.0% FS | |
| | H ₂ S | 0-1,000ppm | ±2.0% FS | |
| | H ₂ S | 0-5,000ppm | ±2.0% FS | |
| | H ₂ S | 0-10,000ppm | ±5.0% FS | |
| | NH ₃ | 0-1,000ppm | ±10.0% FS | |
| | H ₂ | 0-1,000ppm | ±2.5% FS | |
| Typical accuracies | All typical accuracies quoted are after calibration | | | |
| *Hydrogen compensated carbon monoxide measurement | Hydrogen cross gas effect on carbon monoxide approximately 1% Do not use where hydrogen is in excess of 10,000ppm | | | |
| Response time, T90 | CH ₄ | ≤10 seconds | | |
| | CO ₂ | ≤10 seconds | | |
| | O ₂ | ≤20 seconds | | |
| | CO | ≤30 seconds | | |
| | H ₂ S | ≤30 seconds | | |
| | NH ₃ | ≤90 seconds | | |
| | H ₂ | ≤90 seconds | | |
| PUMP | | | | |
| Flow | 550 ml / min typically | | | |
| Flow fail point | -200 mbar vacuum - user settable | | | |
| Maximum vacuum restart | -375 mbar approximately with flow rate of approx 80ml / min | | | |

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

TECHNICAL SPECIFICATIONS *CONTINUED*

| FACILITIES | |
|---|--|
| Temperature measurement | -10°C to +75°C with optional probe |
| Temperature accuracy | ±0.5°C with optional probe |
| Flow from borehole | 0-20 l/hr internal measurement (optional) |
| Flow from borehole accuracy | ±0.3 l/hr |
| Alarm | User selectable alarm levels |
| Communications | Via USB lead or wireless Bluetooth** |
| Relative pressure measurement | ±500 mbar |
| Relative pressure accuracy | ±4 mbar typically (should be zeroed before reading) to ±15 mbar max |
| Barometric pressure measurement | 500 to 1500 mbar, ±5 mbar accuracy |
| GPS sensor | Location and positioning (optional) |
| Available memory | 2,000 IDs, 4000 readings** |
| ENVIRONMENTAL CONDITIONS | |
| Operating temperature range | -10°C to +50°C |
| Atmospheric pressure range | 700 to 1200 mbar |
| Relative humidity | 0-95% non condensing |
| Case seal | IP65 |
| PHYSICAL | |
| Weight | 1.6kg |
| Size | L 220mm, W 155mm, D 60mm |
| Case material | ABS / polypropylene with rubber over-moulding |
| Keys | Alpha-numeric keypad with "tactile" membrane |
| Display | Ultra-clear high resolution 4.3" full colour TFT |
| Connections | Colour coded gas inlet, outlet and pressure ports Waterproof USB port, anemometer and charger / temperature probe connections |
| Gas sample filters | External user changeable 2.0µm ptfе water traps |
| CERTIFICATION RATING | |
| ATEX marking | II 2G Ex ib IIA T1 Gb (Ta = -10°C to +50°C) |
| MCERTS | MC130238 |
| ISO17025 | Calibration to UKAS certificate number 4533 |
| CSA | Ex ib IIA T1 (Ta= -10°C to +50°C) (Canada), AEx ib IIA T1 (Ta= -10°C to +50°C) (USA) |
| ** Gas Analyser Manager software required. | |
| Important note: The information in this document is correct at the time of generation. We do, however, reserve the right to change the specification without prior notice as a result of continuing development. | |



© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.