GA3000 PLUS
FIXED GAS ANALYSER





Anaerobic digestion
Biogas
Landfill gas

GA3000 PLUS

The ATEX certified GA3000 PLUS builds on field-proven, robust gas analysis technology to offer cost effective online monitoring with local data outputs.

Features

- CH_4, CO_2 and O_2 measurement
- Optional H_2S, H_2 and CO measurement
- Multi-point sampling (up to 3 gas sample points)
- H_2S ranges from 0-50ppm to 0-10,000ppm
- Monitor before and after desulphurisation
- Continuous monitoring option[1]
- Large and clear back-lit display
- 4-20mA outputs for each gas
- Modbus communication
- Optional profibus communication
- IP65 rated stainless steel enclosure
- ATEX certified for use in zone 2 areas
- Optional auto-drain pump for moisture removal



Benefits

- No training required
- Low cost of ownership
- Calibration accredited to ISO 17025
- Quick and easy self-installation
- Compact self-contained system
- Moisture removal included as standard
- Zero service downtime
- Field proven equipment
- Simple user calibration

© 2013 Geotechnical Instruments (UK) Ltd, Sovereign House, Queensway, Leamington Spa, Warwickshire, CV31 3JR. Tel: +44 (0)1926 338111
Visit our website at www.geotechuk.com

GA3000 PLUS				
GENERAL SPECIFICATION				
Number of sampling points	1-3			
Gases to be monitored	CH_4, CO_2 and O_2 with optional H_2S, H_2 and CO (choice of up to 5)			
Reading intervals	User definable, with a continuous CH_4, CO_2 and O_2 option available			
Operating temperature range	0°C to +50°C without heater, -20°C to +50°C with heater			
POWER				
Mains options	110-230 VAC 50/60 Hz			
Consumption	0.2A ± 5% without heater, 0.42A ± 5% with heater			
Instrument backup memory	Lithium manganese backup battery for memory retention			
GAS RANGES				
Gases measured	CH_4 and CO_2 O_2 $H_2S/H_2/CO$	By dual wavelength infrared cell with reference channel By internal electrochemical cell By internal/external electrochemical cell		
Range	CH_4 CO_2 O_2 H_2S H2 CO	0-100% 0-100% 0-25% 0-50ppm, 0-200ppm, 0-500ppm, 0-1,000ppm, 0-5,000ppm or 0-10,000ppm 0-1,000ppm 0-1,000ppm		
Typical accuracy - after calibration*		0-5% vol	5-15% vol	15% FS
	CH_4	±0.5% (vol)	±1.0% (vol)	±2.0% (vol)**
	CO_2	±0.5% (vol)	±1.0% (vol)	±2.0% (vol)
	O_2	±1.0% (vol)	±1.0% (vol)	±1.0% (vol)
H_2 and CO typical accuracy - after calibration	H_2	0-1,000ppm	±1.5% FS	
	CO	0-1,000ppm	+3.0% FS	
H_2S typical accuracy - after calibration*	H_2S	0-50ppm	±1.5% FS	
	H_2S	0-200ppm	±1.5% FS	
	H_2S	0-500ppm	±2.0% FS	
	H_2S	0-1,000ppm	±2.0% FS	
	H_2S	0-5,000ppm	±100ppm or 5% of reading (if greater)	
	H_2S	0-10,000ppm	±200ppm or 5% of reading (if greater)	
*plus accuracy of calibration gas used **when above 70% of concentration between temperatures of 41°C and 50°C the accuracy is up to +3.8%				
Response time, T90	CH_4 CO_2 O_2 H2 CO	≤20 seconds ≤20 seconds ≤20 seconds <50 seconds <40 seconds	H2S (0-50ppm) H2S (0-200ppm) H2S (0-500ppm) H2S (0-1,000ppm) H2S (0-5,000ppm) H2S (0-10,000ppm)	≤30 seconds ≤35 seconds ≤35 seconds ≤35 seconds ≤40 seconds ≤40 seconds
Cell lifetime	O_2 cell is 3 years in air, all other cells 2 years in air			

Geotech
A subsidiary of LANDTEC

Sales office:
Tel: +44 (0)1926 338111
Fax: +44 (0)1926 338110
Email: sales@geotech.co.uk

Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

GA3000 PLUS continued	
PUMP	
Flow	300ml/min typically
Flow-fail point	-375 mbar vacuum
Maximum vacuum restart	-375 mbar
COMMUNICATIONS	
Output channels	Up to four analogue 4-20mA output channels plus Modbus digital output, optional profibus module
Alarm notifications	2 user-definable alarms can be triggered when above or below a set value, recovery values can also be defined. (Alarm option only available on single sample point systems)
Relay outputs	Single pole changeover 6A 250V relay volt free
PHYSICAL	
Weight	36.5kg
Size	650 x 600 x 210mm (with supplied wall mounting brackets)
Enclosure	Stainless steel, 600 x 600 x 210mm, IP65 rated
Operation keys	Membrane panel keypad
Display	Liquid crystal display, 40 x 16 characters Fibre optic woven back-light for low light conditions
Moisture removal filters	User replaceable microfibre filter
Heater option	Optional 100W mains powered ATEX certified heater
CERTIFICATION RATING	
ISO17025	Calibrated under UKAS accreditation (certificate number 4533)
ATEX	 II 3 G Ex nA IIA T1 Gc (-20°C ≤ Ta ≤ +50°C)
BS EN 61010	Safety requirements for electrical equipment for measurement, control, and laboratory use
BS EN 50270: 2006	Electromagnetic compatability - electrical apparatus for the detection and measurement of combustible gases, toxic gases or oxygen

[1] Continuous option will include a minimum 3 minute daily air purge

Geotech
A subsidiary of LANDTEC

Sales office:
Tel: +44 (0)1926 338111
Fax: +44 (0)1926 338110
Email: sales@geotech.co.uk

Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.